

EFFECTIVE LEVELS OF ACTIVATED CARBON ADSORPTION

This chart has been developed to relay general activity information of activated carbon and should *not* be used alone for accurate filter design purposes. This information should be helpful as you initially search for the optimum solution to you filtering needs.

As you review this chart, please note the following facts:

- Activity is a term used to describe a standard test which determines the
 effective adsorptive capacity of a sample of activated carbon with a given
 substance.
- Generally, the adsorptive capacity of any activated carbon is higher for adsorbates (substances) of increasing molecular weight and boiling points.
- The effective life of activated carbon depends on the type and quantity of the compounds (substances) to be adsorbed and coming in actual contact with the activated carbon (dwell time).
- The substances listed here encompass specific chemical compounds, classes of compounds and mixtures of variable composition. The levels assigned to specific substances represent "typical" adsorptive effectiveness. Actual applications using activated carbon to adsorb the same substances may vary depending on numerous environmental conditions.
- The numerical levels assigned here represent the following:
 - High adsorptive capacity with substance listed activity of activated carbon typically will run 20% or more of the activated carbon's media weight.
 - Satisfactory adsorptive capacity with substance listedactivity of activated carbon typically will run 10% or more of the activated carbon's media weight.
 - Borderline adsorptive capacity with substance listedactivity of activated carbon typically will run 5% or more of the activated carbon's media weight.
 - Low adsorptive capacity with substance listed- activity of activated carbon typically will run less than 5% of the activated carbon's media weight.

Substance	Molecular Weight	Approx. Activity Level	Typically Found In:			
	Methane Series					
Methane	16.04	1	Illuminating Gas			
Ethane	30.07	1	Illuminating Gas			
Propane	44.09	2	Heating Gas			
Butane	58.12	2	Heating			
Pentane	72.15	3	Light Naphtha			
Hexane	86.17	3	Gasoline			
Heptane	100.20	4	Gasoline			
Octane	114.23	4	Gasoline			
Nonane	128.25	4	Kerosene			
Decane	142.28	4	Kerosene			

Substance	Molecular Weight	Approx. Activity Level	Typically Found In:
	Acetylen	e Series	
Acetylene	26.04	1	Welding, Cutting
Propyne	40.06	2	
Butyne	54.09	2	
Pentyne	68.11	3	
Hexyne	82.14	3	
	Ethylen	e Series	
Ethylene	28.05	1	Illuminating Gas, Anesthetic
Propylene	42.08	2	Coal Gas
Butylene	56.10	2	
Pentylene	70.13	3	
Hexylene	84.16	3	
Heptylene	98.18	4	
Octalene	112.21	4	
	Benzen	e Series	
Benzene	78.11	4	Benzol, Paint Solvent & Remover
Toluene	92.13	4	Manufacture of TNT
Xylene	106.16	4	Solvent
	Other Su	bstances	
Isoprene	68.11	3	Solvent
Turpentine	136.23	4	
Naphthalene	128.16	4	Moth Balls
Phenol	94.11	4	Plastic Ingredient
Methyl Alcohol	32.04	3	Wood Alcohol
Ethyl Alcohol	46.07	4	Grain Alcohol
Propyl Alcohol	60.09	4	
Butyl Alcohol	74.12	4	
Amyl Alcohol	88.15	4	Fusel Oil
Cresol	108.13	4	Ingredient of Creosote Wood Preservative
Menthol	156.26	4	
Formaldehyde	30.03	1	Disinfectant, Plastic Ingredient
Acetaldehyde	44.05	2	
Propionaldehyde	58.08	3	
Acrylaldehyde	56.06	3	Acroloin, Burning Fats
Butyraldehyde	72.10	4	
Valericaldehyde	86.13	4	
Crotonaldehyde	70.09	4	Solvent, Tear Gas

Approx.

Note:

This Information is courtesy of Columbus Industries and Duraflow Industries as the filter manufacturer

Substance	Molecular Weight	Approx. Activity Level	Typically Found In:			
Ot	Other Substances (Continued)					
Formic Acid	46.03	2				
Lactic Acid	90.08	3	Sour Milk			
Acetic Acid	60.05	4	Vinegar			
Propionic Acid	74.08	4				
Butyric Acid	88.10	4	Sweat, Body Odors			
Valeric Acid	102.13	4	Sweat, Body Odors			
Acrylic Acid	76.06	4				
Caprylic Acid	144.21	4	Animal Odors			
Pamitic Acid	256.42	4	Palm Oil			
Methyl Acetate	74.08	3	Solvent			
Ethyl Acetate	88.10	3	Lacquer Solvent			
Propyl Acetate	102.13	4	Lacquer Solvent			
Butyl Acetate	116.16	4	Lacquer Solvent			
Amyl Acetate	130.18	4	Lacquer Solvent			
Acetone	58.08	3	Solvent			
Methyl Ethyl Ketone	72.10	4	Solvent			
Diethyl Ketone	86.13	4	Solvent			
Dipropyl Ketone	114.18	4	Solvent			
Methyl Ether	46.07	3				
Ethyl Ether	74.12	3	Ether-Medical			
Propyl Ether	102.17	3				
Butyl Ether	130.23	4				
Amyl Ether	158.28	4				
Methyl Acrylate	86.09	4	Apt to Polymerize			
Ethyl Acrylate	100.11	4	Apt to Polymerize			
Methyl Mercaptan	48.10	4	Garlic, Onion, Sewer			
Ethyl Mercaptan	63.13	4	Garlic, Onion, Sewer			
Propyl Mercaptan	76.15	4	Garlic, Onion, Sewer			
Eucalyptol	154.25	4				
Camphor	152.23	4				
Methyl Chloride	50.49	3	Refrigerant			
Ethyl Chloride	64.52	4	Local Anesthetic			
Propyl Chloride	78.54	4	Local Anesthetic			
Butyl Chloride	92.57	4	Local Anesthetic			
Methylene Chloride	84.94	4				
Chloroform	119.39	4	Anesthetic, Solvent			
Carbon Tetrachloride	153.84	4	Cleaning Fluid, Solvent			
lodoform	393.78	4	Antiseptic			
Phosgene	98.92	4	Poison Gas, Reagent			
Pyridine	79.10	4	Burning Tobacco			
Indole	117.14	4	Excreta			
Skatole	131.17	4	Excreta			
Nicotine	162.23	4	Tobacco			
Nitrobenzene	123.11	4	Oil of Bitter Almonds, Oil of Mirbane			

Substance	Molecular Weight	Approx. Activity Level	Typically Found In:
Urea	60.06	3	Urine
Uric Acid	168.11	4	Urine
Putrescine	88.15	4	Decaying Flesh
Chlorine	70.91	3	May Partially Hydrolyze to HCL
Bromine	159.83	4	May Partially Hydrolyze to HBr
lodine	253.84	4	May Partially Hydrolyze to HI
Hydrogen Fluoride (Hydrofluoric Acid)	20.01	1	Approximate activity
Hydrogen Chloride (Hydrochloric Acid)	36.47	2	levels given are for dry substances. In presence of water,
Hydrogen Bromide	80.92	2	values are
Hydrogen lodide	127.93	2	approximately doubled.
Nitrogen Dioxide	46.01	2	May Partially Hydrolyze to HNO ₃
Nitrogen Tetraoxide	(92.02)		
Nitric Acid	63.02	2	
Sulfur Dioxide	64.06	2	Oxidizes to SO ₃
Sulfur Trioxide	80.06	3	Hydrolyzes to H ₂ SO ₄
Sulfuric Acid	98.08	4	
Adhesives		4	
Ammonia		2	
Asphalt Fumes		4	
Automobile Exhaust		3	
Diesel Fumes		4	
Bathroom Smells		4	
Bleaching Solutions		3	
Cleaning Compounds		4	
Cooking Odors		4	
Hospital Odors		4	
Household Smells		4	
Jet Fuel Fumes		4	
Kitchen Odors		4	
Mildew		3	
Mold		3	
Ozone		4	
Paint & Redecorating Odors		4	
Smog		4	
Stale Odors		4	

Note:

This Information is courtesy of Columbus Industries and Duraflow Industries as the filter manufacturer